

AV3850SU

The AV3850SU is designed for workgroups who have heavy-duty scanning needs. This scanner is easy to operate and has a fast scanning speed of 50 pages per minute for simplex and 100 images per minute for duplex mode.

The combination of fast document feeding and true 600 dpi resolution is the basis for good image quality. The AV3850SU is a powerful and functional addition for your workgroup, offering the advantage of both **USB 2.0** and **SCSI-II interface**.



Avision

Specifications

| | |
|------------------------|--|
| Document feeding mode | Flatbed, ADF (straight), duplex |
| Technology | CCD, light source: CCFL |
| Optical resolution | 600 dpi |
| Image type | B & W: line art, halftone; Error Diffusion |
| Grey scale/colour mode | 8/24 bits |
| Colour depth | 48 bits |
| ADF capacity | 50 sheets |
| Double feed control | due to length |
| Interface | USB 2.0, SCSI-II |
| Paper format | ADF minimum 4.5 x 5.5 in / 114 x 139 mm ADF maximum 8.5 x 14 in / 215 x 355 mm Flatbed maximum 8.5 x 11.69 in / 215 x 296 mm |
| Scanning speed | 50 PPM / 100 IPM (200 dpi @ A4, b/w), 30 PPM / 50 IPM (150 dpi @ A4, colour) |
| Operating system | Win98SE/ME/2K/XP, Mac OSX (optional) |
| Software | PhotoSuite, PaperPort 9.0, AVScan, AVCapture, TWAIN & ISIS driver |
| Power supply | Input: 100 ~ 240 VAC, 50/60 Hz, output: 24 V, 2.0 A |
| Power consumption | < 48 W |
| Dimensions, weight | 198 x 566 x 348 mm (without tray), 7.55 kg |
| Daily duty cycle | 2500 pages |



Specifications are subjects to change without prior notice.